

**ATLANTIC RESIDENTIAL
INDIGO POMPANO BEACH
CPTED NARRATIVE**

November 29, 2023

Project Location: 777 Isle of Capri Circle, Pompano Beach, FL 33069

Project Description: The Atlantic Residential project is located at 777 Isle of Capri Circle south of Palm Aire Drive and East of Main Street. Indigo Pompano Beach is a multi-family residential project located on a 12.78-acre parcel featuring nine (9) Multi-Family Buildings, 423 residential units between 2-story and 5-stories tall. The site also features (6) ancillary 1-story garage-bay structures, a centralized clubhouse, and amenity areas for passive green space, recreational court, and pool. Below is a description of how the project addresses each crime prevention through environmental design ("CPTED") principle. The project team prepared a CPTED plan and attached it to this application package as Sheet SP-201, SP-202, and SP-203.

1. **Natural/Electronic Surveillance:** This project adheres to this principle by the organization of physical features, activities, and people in such a way as to maximize visibility to and from the site. These elements of the project design further create a perception of safety by presenting a fear of detection for potential intruders. This project implements this principle in the following ways:
 - a. A CCTV security system with electronic access control at ground floor of each building will be installed for the project at the time of substantial completion.
 - b. Camera locations will be focused on main entrances, building perimeters, and high-use areas. CPTED plan currently indicates CCTV security camera locations will be installed and coordinated with a security consultant at the time of building permits.
 - c. Video and security cameras will be monitored remotely. At time of building permitting, specific camera locations will be proposed showing complete field of coverage.
 - d. Ensure all lighting (and cameras) are strategically placed so they will not be obstructed by the growth of existing, or installation of future landscaping.
 - e. Developers/ contractors will consult with camera system designers, installers and BSO CPTED Team with final camera plans prior to installation.
 - f. CCTV cameras must be strategically located for maximum overlapping active and passive observation. Placement in strategic locations is to increase surveillance and reporting of suspicious or illegal activity including dangerous incidents.
 - g. Large CCTV viewing monitors are recommended for optimal viewing. They should be placed strategically wherever they would receive the most viewing from personnel traffic such as at the maintenance office.
 - h. Ensure all cameras are strategically placed so they will not be obstructed by the growth of existing or installation of future landscaping.
 - i. Ensure lighting placement will enhance rather than conflict with camera placement. Avoid placing a light that would concentrate light directly into a camera lens thereby causing interference in operational efficiency.
 - j. Install motion activated security cameras up to and at the perimeter boundaries of ancillary buildings, parking areas, and/or locations that do not have frequent building access. These will help deter criminal activities such as burglary, auto-theft, robbery, sexual assault & battery, etc.

www.KEITHteam.com

PZ23-12000039
02/21/2024

Any blind areas not covered by security cameras, including detached garages and vehicular entrance gates, must have corner security mirrors installed to assist in visibility around blind spot corners to deter/ prevent undetected trespass intrusion and/ or concealment/ ambush opportunities.

Lighting:

- a. An adequate functioning and well-designed lighting system will keep areas well-lit at night to establish a sense of security for the site.
- b. The entire site will feature adequate lighting, per the standards of the code.
- c. Foot-candle illumination will be increased at building entrances and high-use areas of the site. Proposed lighting does not conflict with proposed landscaping.
- d. Reduction of shadows and glare will be achieved as best possible.
- e. The entire site will feature adequate lighting, per the standards of the code. This includes the exterior dumpster area in a manner that offers passive surveillance for the neighboring building. Any trash rooms located within the building will be secure and feature adequate lighting.
- f. Security lighting should usually be primarily concentrated at gateways, doorways & windows; it should not over-illuminate or create shadows.
- g. Design out any potential landscaping and lighting conflicts to avoid existing or future obstructions to natural or mechanical lighting and surveillance.

Sidewalks:

- a. Site designers created a sidewalk circulation network that offers multiple pedestrian routes, eliminating dead-ends and entrapment zones within the project.
- b. Clear lines of sight to and from private and public areas. The use of large openings with the building set close to the street will create a sense of place.
- c. All non-residential space within the building offers controlled access. Natural surveillance is provided through one point of access, so users are closely monitored.

Landscaping:

- a. The proposed landscaping is designed to reduce obstructions to the building entrances, with taller vegetation and trees planted away from entrances and walkways.
- b. Note that young immature trees with 6" inch or less diameter trunks are excluded from this condition ONLY WHILE MATURING per code,
- c. The proposed landscaping is designed to reduce obstructions to the building entrances, with taller vegetation and trees planted away from entrances and walkways.
- d. Maintain a 2' to 2.5' foot maximum height for all hedges, bushes, low plants, and ground cover around glass windows.
- e. At time of mature tree height, an 8' - feet clear tree trunk for canopy trees and tall plants without any obstructive limbs or foliage hanging down below 8' feet that would in the present or future obstruct natural and electronic surveillance. This principle will be focused around vehicle entry points and around building entry points throughout the project.

PZ23-12000039
02/21/2024

- f. Ensure to design out all landscaping and lighting conflicts to avoid existing or future obstructions to Natural or Electronic Surveillance which frequently occurs due to a lack of CPTED/ Security Strengthening planning and design experience in this specialized field.
- g. Ensure to design out existing or potential concealment and ambush points to deter/ prevent criminal activity. Again, planning and design experience in this area is vital.
- h. Note that young immature trees with 6" inch or less diameter trunks are excluded from this condition ONLY WHILE MATURING per code,

2. Physical/Natural Access Control: This principle focusses on maintaining control and preventing potential criminals from gaining the opportunity to commit criminal activity. The project achieves this by implementing the following concepts:

- a. The site is accessed by vehicles at two locations. These locations are designed as a two-way main entrance/exit where incoming/outgoing traffic can be monitored to and from the surface parking areas.
- b. Any exterior ground level architectural abstract design features should not have easily accessible horizontal bars that could be used to facilitate climbing over and breaching any security fencing. Use narrow spacing between vertical bars to prevent providing footholds.
- c. Solid walls, specifically those used as perimeter / privacy boundaries, should not have a flat top and should be designed with an angled, beveled, curved or otherwise shaped top to deter easy climbing over which is a potential trespassing/ breaching vulnerability, and/ or to deter sitting and loitering upon which could also be a potential fall and injury hazard. Signage prohibiting trespass or sitting upon walls should be included in the design as necessary.
- d. All exterior doors must have non-removable door hinge pins. The project will feature electronic controlled access systems with key fobs for common area doors.
- e. A Rollup Gate design will be implemented for the one-story accessory garage buildings to prevent unauthorized access.
- f. Residents with FOB's/ Smartcards should have electronic access control to the front entrance doors, the garage entrance door, the stairwells, and the trash/ garbage room.
- g. Parking lot spaces are clearly identified with pavement marking and signage.
- h. Towing signage will be displayed to prevent unauthorized parking or abandonment of vehicles.
- i. The project does not anticipate having any type of late-night business as defined by the City of Pompano Beach Land Development Code as a place of retail or commercial business that is open for business to the public at any time between the hours of 11:00 p.m. and 5:00 a.m. and which does not meet the definition for a Convenience Business.
- j. The project will feature smart card reader technology for building access, which will also allow law enforcement efficient access in the event of an emergency.
- k. Adequate signage will be posted, such as towing signs, to prevent un-authorized parking and vehicle abandonment within the project site. A towing policy will be strictly enforced.
- l. Management office door must have a security viewer (peephole) or reinforced security window.
- m. a 180-degree peephole viewer will be implemented for each condo unit door within the residential component of the project. Each ground floor common area door will feature an impact rated viewing glass window.

PZ23-12000039
02/21/2024

All solid exterior doors at main building entrances will have an audible AND video intercom pager capable of monitoring the area outside the door. This feature provides an opportunity to monitor and surveil the exterior prior to exiting to avoid being ambushed upon exiting and becoming a victim of robbery or other crimes.

- 3. Territorial Reinforcement:** This principle includes defining public vs. private property. Regular occupants establish a sense of ownership of private space and notice potential criminal activity before it happens. The project achieves this by implementing the following concepts:
 - a. Perimeter landscape further separates public vs private space, specifically along the property's all sides of the project.
 - b. Project will be participating in the Broward Sheriff's Office No Trespass Program.
 - c. Submit a Broward Sheriff's Office No Trespass Program Affidavit simultaneously with the application.
 - d. Way-Finding signage must be clear and prominently posted in appropriate areas indicating safe directional travel routes to warn and avoid users from getting confused and wandering into potentially unsafe and dangerous areas that might expose them to increased safety and security risks.
 - e. Post sufficient BSO No Trespass Signage so that it is readily available at all sides of the property: North, South, East and West.
 - f. Prominently post signs securely using robust fasteners.
 - g. Ensure all exterior water outlet spigots have a secure locking cap to deny unauthorized use by vagrants, etc. who loiter and trespass to wash their bodies and clothes.
 - h. Any publicly accessible seating benches or platforms should be designed to deter loitering/ sleeping by vagrants/ trespassers. An example would be to incorporate individual seating on a bench by including arm bars between designated single seating positions. Large horizontal platforms should incorporate an anti-loitering/ sleeping design feature.
- 4. Maintenance:** Vandalism is a criminal activity which typically coincides with lack maintenance and abandonment. Maintenance is an important factor in preserving a safe environment and this project aims to satisfy this principle in the following ways:
 - a. Landscape maintenance of the surrounding areas will indicate an adequate functioning project, therefore promoting the sense of occupancy, further deterring criminal activity.
 - b. The grounds will be clean and clear of debris.
 - c. Maintenance Staff will take notice of any damage or hazards within the maintained areas. They will perform quick repairs to keep the site clean and safe.
 - d. Graffiti will be cleaned or painted over as quickly as possible.
 - e. If applicable, all exterior power outlets will have a lock or power secure internal cut-off switch to deny unauthorized access.
- 5. Activity Support:** Activity support does exactly what the title presents; to provide support to the surrounding areas by establishing a presence of people and activity. Criminals are less likely to commit a crime if they know other people may be watching. The project adheres to this principle in the following way:
 - a. Pedestrian activity zones are created with benches and resting areas throughout the project.

PZ23-12000039 Patio areas and connections to the pedestrian network will promote activity on the property, further supporting the principle of natural surveillance as people will be aware of what is happening in the surrounding areas.
02/21/2024

6. Lot, adjacent access egress and perimeter:

- a. Dumpster areas will be internal to the building, secured with Access Control, and video surveillance.
- b. Only if applicable such as with a garage) An Access Control vehicular gate entrance into the parking garage / development will deter and help prevent trespass opportunities. These entrances must be under video surveillance.

7. Miscellaneous: CPTED & Security Strengthening:

- a. Place bike storage racks (if any) close to the main access doors providing convenience and maximum Natural and Electronic Security Surveillance.
- b. If the building/ development has a Wi-Fi system, it needs to be encrypted and password protected. An open Wi- Fi system will attract non-legitimate users to loiter and use the open free Wi-Fi.
- c. Any exterior storage tanks utilized for keeping contents under pressure and / or containing any flammable or hazardous contents must be properly secured against any acts of vandalism, theft or misuse of any kind. Only use fire code approved security systems / mechanisms.
- d. Viewable monitor(s) should be placed in a central area to provide clear indication that video surveillance is in use & broadcasting to all that crimes will be discovered & recordings used as evidence for arrest & prosecution.
- e. Viewable monitor(s) should capture & display public points of ingress & egress. (Camera feeds that are to remain off limits to staff for internal security reasons do not have to be displayed on the Viewable monitor.)
- f. Costly equipment such as ground floor exterior air conditioning units (if any) must be clearly and permanently marked with serial numbers and images of equipment and serial stored for criminal investigation. This information must be readily available in the event of a theft or burglary to help law enforcement investigators to quickly track and recover the stolen items. The equipment must be secured robustly to deter/ prevent theft.
- g. Commercial, Industrial and Multi-Family Residential exterior wall surfaces along the building perimeter must be treated with a graffiti resistant resin up to 8 feet to prevent vandalism. Graffiti vandalism is chronic these days and therefore becomes very expensive to repeatedly address. It leads to unsightly blight conditions, and often also costly Code Enforcement violations, therefore incorporating it into the project beforehand is financially strategic and vital to project sustainability.

PZ23-12000039
02/21/2024

CPTED SUPPLEMENTAL STRENGTHENING NOTES: PER BSO PRE-APP COMMENTS RECEIVED ON 9/5/2023

- a. Fences, gates and/ or any exterior ground level architectural abstract design features should not have easily accessible horizontal bars that could be used to facilitate climbing over and breaching any security fencing. Use narrow spacing between vertical bars to prevent providing footholds.
- b. Solid walls, (if any) specifically those used as perimeter / privacy boundaries, should not have a flat top and should be designed with an angled, beveled, curved or otherwise shaped top to deter easy climbing over which is potential trespassing/ breaching vulnerability, and/ or to deter sitting and loitering upon which could also be a potential fall and injury hazard. Signage prohibiting trespass or sitting upon walls should be included in the design as necessary.
- c. Solid walls, (if any) specifically those used as perimeter / privacy boundaries, should not have a flat top and should be designed with an angled, beveled, curved or otherwise shaped top to deter easy climbing over which is a potential trespassing/ breaching vulnerability, and/ or to deter sitting and loitering upon which could also be a potential fall and injury hazard. Signage prohibiting trespass or sitting upon walls should be included in the design as necessary.
- d. Include anti-pry robust security bar device on any ground or second level sliding glass doors (if any).
- e. For commercial and industrial: burglary / intrusion/ sensor alarms must be activated whenever the business is closed, or all authorized personnel are out of the business.
- f. Describe access key control security system - general description only, avoid specific location of key storage safe.
- g. Centralized access control system with individual, programmed fobs as credentials to access all common doors and gates. Credentials can be canceled in case of loss/theft, and use of credentials can be tracked and users identified through system logs.
- h. Key security office/ room/ key storage closet door must have an alarm and robust mechanical locking system.
- i. A surveillance camera must monitor the office key storage area.
- j. An access control vehicular gate entrance into the parking garage/ development will deter and help prevent trespass opportunities. These entrances must be under video surveillance. (please clarify if this development will be secured with vehicle access control gates at points of entry/exit).

PER BSO DRC COMMENTS RECEIVED ON 11/1/2023

1. CPTED Lighting Standards
 - a. All Structures: Install vandal proof/ resistant motion-sensor security alert lights over all exterior unit doors and overhangs (if any), including main entrance ways, garages, storage doors, storage sheds (if any), etc.

RESPONSE: We propose the installation of vandal proof/resistant light fixtures over all exterior unit doors and overhangs to be activated by photocells, so these areas are constantly illuminated from dusk to dawn. These will be designed with appropriate optics and temperature of light, so they are not harsh and inconvenient to unit occupants. We propose this solution in lieu of motion-sensor lights in order to prioritize comfort of

PZ23-12000039
02/21/2024

residents, who tend to consider lights going on and off outside their unit windows as distracting and invasive.

2. Security Strengthening, Natural Surveillance and Access Control - Doors, Windows, Overhangs, Perimeter Fences and Walls, Etc.
 - a. Fences, gates and / or any exterior ground level architectural abstract design features should not have easily accessible horizontal bars that could be used to facilitate climbing over and breaching any security fencing. Use narrow spacing between vertical bars to prevent providing footholds.
 - b. Solid walls, (if any) specifically those used as perimeter / privacy boundaries, should not have a flat top and should be designed with an angled, beveled, curved or otherwise shaped top to deter easy climbing over which is a potential trespassing/ breaching vulnerability, and/ or to deter sitting and loitering upon which could also be a potential fall and injury hazard. Signage prohibiting trespass or sitting upon walls should be included in the design as necessary.
 - c. Solid walls (if any) that are low to the ground & used as symbolic barriers should have a topside shape to prevent the potential for misuse, damages &/or vandalism inflicted by skateboarding, rollerblading, bicycling, etc. Examples of such shapes include, but are not limited to angled, curved, ridged, beveled &/or incorporated with cleats, intermittent spacing or other architectural design to dissuade such unauthorized activity.
 - d. Include anti-pry robust security bar device on any ground or second level sliding glass doors (if any).

RESPONSE: Comments acknowledged, to be incorporated to building and hardscape design.

3. Security Strengthening - Burglar Security Alarms/ Safes – Physical & Mechanical Security Strengthening

- a. Install hard wired burglar security alarms, or at the minimum prewire each residential unit for burglar alarms as residential units are often targets of thefts, frauds, burglaries, robberies, etc. Safes are also strongly recommended.
- b. For Commercial and Industrial: Burglary / Intrusion / Sensor alarms must be activated whenever the business is closed, or all authorized personnel are out of the business.
- c. For Commercial including COMMERCIAL RESIDENTIAL/ Hotels/ Multi-Family with Security/ Front Desk Receptionists / Hosts (if any): Install a fixed concealed silent panic duress alarm at main entrance AND a portable lanyard for redundancy in the event the fixed alarm is compromised due to the fixed alarm post being vacant, or for any serious incident such as an active killer or other emergency.

RESPONSE: As it pertains to concealed silent panic duress alarm at main entrance and portable lanyard, request is acknowledged, and items will be incorporated to access control system design. As it pertains to burglar security systems, residential units in levels 2 through 5 are only reachable through internal corridors, which are covered by multiple layers of general CCTV and access control (fobbed doors and gates). Therefore, we propose pre-wiring for burglar security alarms in ground floor units only.

4. Key Security: Access Control and Security Strengthening (For businesses with numerous keys on site such as residential or commercial management offices, warehouses with numerous vehicles, trucks, etc., valuable assets on site including equipment, tools, supplies, etc., property management offices, realtors, car dealerships, restaurants, valets, etc.)

- a. Describe access key control security system - general description only, avoid specific location of key storage

PZ23-12000039
02/21/2024

- b. Key security office/ room/ key storage closet door must have an alarm and robust mechanical locking system.
- c. A surveillance camera must monitor the office key storage area.

RESPONSE:

- All vehicular and pedestrian gates and building exterior entry doors accessible to residents will be provided with an electric strike or mag lock, which will be controlled by a fob/card/RFID reader.
- Moreover, each unit entry door will be provided with a keyless locking device, also controlled by a fob/card/RFID tag.
- All these credentials will be created/programmed by registered on-site property management staff, only once and at the time a resident move into the community. Lost and obsolete credentials will be immediately voided.
- Each of these credentials allow identification of user responsible for each single event (door/gate opening), allowing all occurrences to be verified and cross-examined with surveillance footage captured by property CCTV system.
- There will be one (1) desktop computer at back office within leasing center (clubhouse) dedicated to the creation of credentials, with necessary software/hardware. Such room will be monitored by a surveillance camera connected to the property CCTV system.

Physical keys to staff-only doors (technical closets, storage, maintenance shop, restricted areas) will be kept at key storage safe within leasing center (clubhouse), and protected by surveillance camera and alarm.

5. Parking Garage &/ or Lot, and Adjacent Access Egress and Perimeters:

- a. An Access Control vehicular gate entrance into the parking garage / development will deter and help prevent trespass opportunities. These entrances must be under video surveillance.

(Please clarify if this development will be secured with vehicle access control gates at points of entry / exit)

RESPONSE: The two (2) vehicular entrances into the development will be surrounded by metal gates (sliding, swinging or lifting opening) that will cover full width of car lanes, and with height consistent with adjacent perimeter fences. Before each entrance gate, an arm gate will be also added to prevent tailgating of unauthorized persons. Both metal and arm gates will be opened by using a fob/card/RFID sticker, which will be provided to residents only. All vehicular gates will be covered by surveillance cameras, connected to the property CCTV system.

6. Miscellaneous: CPTED & Security Strengthening

- a. Elevator (if any) - Access Controlled by 1st floor FOB, include blind spot convex mirrors and electronic surveillance and a panic button.

RESPONSE: First floor access to elevator will be in enclosed location (lobby, vestibule pr corridor) accessible only with resident credentials (fob/card/RFID tag). Convex mirrors will be added where and if blind spots are created, and panic button will be provided in each elevator cab.