

3	ZONING REGULATIONS AND AREA REQUIREMENTS - FOR ZONING B3			
ZONING DESIGNATION		ALLOWED / REQUIRED		PROVIDED
CITY OF POMPANO BEACH		MUNICODE		APPENDIX A
EXISTING ZONING DISTRICT: B-3 (GENERAL BUSINESS)		B-3 (GENERAL BUSINESS)		B-3 (GENERAL BUSINESS)
FUTURE LAND USE: C (COMMERCIAL)				

PERMITTED USE		ALLOWED / REQUIRED		PROVIDED
CITY OF POMPANO BEACH		MUNICODE		APPENDIX A
SEE APPENDIX A FOR COMPLETE CONSOLIDATED USE TABLE		DWELLING, MIXED-USE		DWELLING, MIXED-USE (RESIDENTIAL + COMMERCIAL)

SITE DIMENSION REQUIREMENTS		ALLOWED / REQUIRED		PROVIDED		
CITY OF POMPANO BEACH		MUNICODE		SECTION 155.5304	SITE WIDTH	SITE DEPTH
LOT AREA SHALL BE DETERMINED BY MEASURING THE TOTAL HORIZONTAL LAND AREA (IN SQUARE FEET) WITHIN THE LOT LINES OF THE LOT		MAX. 80% OF SITE AREA (MAY INCREASE BY UP TO 20%)		EXISTING BUILDING	10,247 SF (10%)	NEW BUILDING
LOT WIDTH SHALL BE DETERMINED BY CALCULATING THE MEAN HORIZONTAL DISTANCE BETWEEN THE INTERIOR SIDE LINES OF A LOT, OR FOR CORNER LOTS, BETWEEN A STREET SIDE LOT LINE AND THE OPPOSITE INTERIOR SIDE LOT LINE, AS MEASURED ALONG A LINE RUNNING ALONG THE MIDPOINTS BETWEEN THE INTERIOR SIDE LOT LINES, OR BETWEEN THE STREET SIDE LOT LINE AND THE OPPOSITE INTERIOR SIDE LOT LINE, AS APPROPRIATE.		0.1 * 102,519 SF = 91.31 (4 SF (BASED ON NET AREA))		38,566 SF (37.62%)	102,519 SF	

LOT COVERAGE (MAXIMUM)		ALLOWED / REQUIRED		PROVIDED
CITY OF POMPANO BEACH		MUNICODE		SECTION 155.5304 & 155.4202.A.1
LOT COVERAGE (EXPRESSED AS A PERCENTAGE OF LOT AREA) SHALL BE DETERMINED BY MEASURING THE TOTAL HORIZONTAL LAND AREA (IN SQUARE FEET) COVERED BY ALL PRINCIPAL AND ACCESSORY STRUCTURES ON THE LOT, DIVIDING THAT COVERAGE AREA BY THE TOTAL LOT AREA (SEE SUBSECTION A ABOVE), AND MULTIPLYING THE RESULT BY 100.		MAX. 80% OF SITE AREA (MAY INCREASE BY UP TO 20%)		EXISTING BUILDING
MULTIFAMILY AND MIXED-USE DEVELOPMENT THAT INCORPORATES RESIDENTIAL MAY INCREASE LOT COVERAGE BY UP TO 20%.		0.1 * 102,519 SF = 91.31 (4 SF (BASED ON NET AREA))		38,566 SF (37.62%)

DENSITY (MAXIMUM)		ALLOWED / REQUIRED		PROVIDED
CITY OF POMPANO BEACH		MUNICODE		SECTION 155.5304 & 155.4202.A.1
DENSITY (EXPRESSED AS DWELLING UNITS PER ACRE) SHALL BE DETERMINED BY DIVIDING THE TOTAL NUMBER OF DWELLING UNITS LOCATED OR PROPOSED ON A LOT BY THE AREA OF THE LOT AREA (SEE SUBSECTION A ABOVE), AND MULTIPLYING THE RESULT BY 43,560. FOR PURPOSES OF DETERMINING MAXIMUM DENSITY, AN ACCESSORY DWELLING UNIT SHALL BE CONSIDERED TO BE A HALF DWELLING UNIT.		48 DU / AC (WITH BONUS)		132 UNITS
ALL DEVELOPMENT PROJECTS IN A COMMERCIAL LAND USE CATEGORY THAT UTILIZE BROWARD COUNTY POLICY 2.6.5.3 OR 2.6.5.4 SHALL RECEIVE UP TO A 50% ZONING DENSITY BONUS. THEY MAY ALSO APPLY FOR MINOR VARIATIONS, OR ADJUSTMENTS, TO CERTAIN DIMENSIONAL OR NUMERICAL STANDARDS OF THIS CODE BASED ON SPECIFIC CRITERIA AS DETAILED IN SECTION 155.2421, ADMINISTRATIVE ADJUSTMENT.		48 DU * 2.354 AC = 108 UNITS		

BUILDING HEIGHT IN FEET (MAXIMUM)		ALLOWED / REQUIRED		PROVIDED
CITY OF POMPANO BEACH		MUNICODE		SECTION 155.5304
THE VERTICAL DISTANCE BETWEEN THE AVERAGE ELEVATION OF THE EXISTING OR PROPOSED FINISHED GRADE AT THE FRONT OF A STRUCTURE TO THE HIGHEST POINT OF A FLAT ROOF, TO THE DECK LINE OF A MANGROVE ROOF, OR TO THE MEAN HEIGHT BETWEEN GABLES AND RIDGE OF A GABLE, HIP, CONE, GAMBLE, OR SHED ROOF.		105'-0"		105'-0"

UNIT SIZE (MINIMUM)		ALLOWED / REQUIRED		PROVIDED		
CITY OF POMPANO BEACH		MUNICODE		SECTION 155.4202.A.1	EFFICIENCY / STUDIO	N / A
SEE TABLE 155.4202.A.1.a.ii: FLOOR AREA PER DWELLING UNIT, MINIMUM (SQUARE FEET)		EFFICIENCY / STUDIO		450 SF	1 BEDROOM UNIT	620 SF
		1 BEDROOM UNIT		575 SF	2 BEDROOMS UNIT	965 SF
		2 BEDROOMS UNIT		750 SF	3 BEDROOMS UNIT	1,225 SF
		3 BEDROOMS UNIT		850 SF	ADDITIONAL BEDROOM	N / A

BUILD-TO-ZONE BUILDING PERCENTAGE		ALLOWED / REQUIRED		PROVIDED
CITY OF POMPANO BEACH		MUNICODE		SECTION 155.4202.A.1
BUILD-TO-ZONE IS THE AREA ON A LOT LOCATED BETWEEN THE MINIMUM AND MAXIMUM SETBACK THAT MUST CONTAIN A PRINCIPAL STRUCTURE, A COURTYARD, PLAZA, OR FORECOURT MAY OCCUPY THE OTHERWISE REQUIRED BUILD-TO-ZONE, IF THE SPACE IS PUBLICLY ACCESSIBLE, PROVIDING BUILDING ACCESS AND A PEDESTRIAN CONNECTION TO THE EXISTING CITY STREET GRID. FENESTRATION REQUIREMENTS FOR ABUTTING FACADES STILL APPLY.		BUILD-TO-ZONE AREA 3,000 SF (100%)		PAVEMENT AREA 1,800 SF (60.00%)
		MINIMUM 60% = 1,800 SF		3,000 SF (100%)

PERVIOUS AREA (MINIMUM)		ALLOWED / REQUIRED		PROVIDED
CITY OF POMPANO BEACH		MUNICODE		SECTION 155.5304 & 155.4202.A.1
THE AREA OF A SITE COVERED BY LIVING PLANT MATERIAL THAT ALLOWS PRECIPITATION TO INFILTRATE DIRECTLY INTO THE GROUND. UP TO 15% OF THE AREA MAY BE COVERED WITH MULCH OR OTHER TYPES OF NON-LIVING PERVIOUS MATERIALS.		20% OF THE NET SITE AREA (MAY REDUCE TO 10%)		22,535 SF (21.98%)
MULTIFAMILY AND MIXED-USE DEVELOPMENT THAT INCORPORATES RESIDENTIAL MAY REDUCE THE PERVIOUS AREA REQUIREMENT TO 10% OF THE TOTAL LOT AREA. LANDSCAPING AND STORMWATER RETENTION REQUIREMENTS STILL APPLY.		0.2 * 102,519 SF = 20,503.8 SF		

PERIMETER LANDSCAPE BUFFER (MINIMUM WIDTH)		ALLOWED / REQUIRED		PROVIDED
CITY OF POMPANO BEACH		MUNICODE		SECTION 155.5203.F.3
PERIMETER BUFFERS ARE INTENDED TO HELP MITIGATE POTENTIAL NEGATIVE EFFECTS OF PROPOSED DEVELOPMENTS ON ADJUTING PROPERTY AND ADJUTING RIGHTS-OF-WAY.		BETWEEN MIXED-USE DEVELOPMENT AND LAND WITHIN A RESIDENTIAL ZONING		10 FEET
		TYPE B BUFFER		MIN. 10 FEET

PERIMETER LANDSCAPE STRIP FOR VUA (MINIMUM WIDTH)		ALLOWED / REQUIRED		PROVIDED
CITY OF POMPANO BEACH		MUNICODE		SECTION 155.5203.D.3.C
PERIMETER LANDSCAPING STRIPS SHALL BE PROVIDED AND MAINTAINED AROUND THE PERIMETER OF A VEHICULAR USE AREA TO SCREEN VIEW OF IT FROM ANY ADJUTING PUBLIC RIGHT-OF-WAY, PRIVATE ROADWAY, ALLEY, PROPERTY, OR WATERWAY IN ACCORDANCE WITH THE FOLLOWING STANDARDS, EXCEPT WHERE SUCH SCREENING IS PROVIDED BY AN INTERVENING ON-SITE BUILDING OR OTHER STRUCTURE AND ON LAND CROSSED BY AN AUTHORIZED VEHICULAR, BICYCLE, OR PEDESTRIAN ACCESSWAY OR LAISEMENT FOR AN UNDERGROUND UTILITY LINE.		10 FEET (ON LOTS GREATER THAN 100 FEET WIDE)		10 FEET

SURFACE PARKING LANDSCAPE ISLAND LOCATION		ALLOWED / REQUIRED		PROVIDED
CITY OF POMPANO BEACH		MUNICODE		SECTION 155.5203.A.B
A LANDSCAPE ISLAND SHALL BE PROVIDED AT EACH END OF EVERY ROW OF PARKING SPACES, WHERE A ROW OF PARKING SPACES CONTAINS TEN OR MORE PARKING SPACES. ADDITIONAL LANDSCAPED ISLANDS SHALL BE PROVIDED AT A SPACING NO GREATER THAN ONE EVERY TEN PARKING SPACES.		AT EACH END OF EVERY ROW OF PARKING SPACES		PROVIDED SEE SHEET A-080
		WHERE A ROW OF PARKING SPACES CONTAINS 10 OR MORE SPACES		

SURFACE PARKING LANDSCAPE ISLAND (MINIMUM LENGTH & WIDTH)		ALLOWED / REQUIRED		PROVIDED
CITY OF POMPANO BEACH		MUNICODE		SECTION 155.5203.A.B
II. EACH LANDSCAPED ISLAND SHALL BE AT LEAST EIGHT FEET WIDE AND AT LEAST AS LONG AS THE ADJACENT PARKING SPACES, WITH THE LONG AXIS OF THE LANDSCAPED ISLAND RUNNING APPROXIMATELY PARALLEL TO THAT OF THE ADJACENT PARKING SPACES.		LENGTH		18 FEET
		WIDTH		8 FEET

FRONT / STREET SETBACK		ALLOWED / REQUIRED		PROVIDED
CITY OF POMPANO BEACH		MUNICODE		SECTION 155.4202.A.1
SETBACK, FRONT YARD		MIN. 0 FEET		20 FEET
THE SHORTEST HORIZONTAL DISTANCE FROM THE FRONT LOT LINE OF A LOT TO THE NEAREST POINT OF A PRINCIPAL STRUCTURE ON THE LOT.		MAX. 30 FEET		

INTERIOR SIDE SETBACK		ALLOWED / REQUIRED		PROVIDED
CITY OF POMPANO BEACH		MUNICODE		SECTION 155.4202.A.1
SETBACK, INTERIOR SIDE YARD		MIN. 0 FEET		10 FEET
THE SHORTEST HORIZONTAL DISTANCE FROM THE INTERIOR SIDE LOT LINE OF A LOT TO THE NEAREST POINT OF A PRINCIPAL STRUCTURE ON THE LOT.				

REAR SETBACK		ALLOWED / REQUIRED		PROVIDED
CITY OF POMPANO BEACH		MUNICODE		SECTION 155.4202.A.1
SETBACK, REAR YARD		MIN. 20 FEET		24'-0"
THE SHORTEST HORIZONTAL DISTANCE FROM THE REAR LOT LINE OF A LOT TO THE NEAREST POINT OF A PRINCIPAL STRUCTURE ON THE LOT.				

SETBACK ENCROACHMENT		ALLOWED / REQUIRED		PROVIDED
CITY OF POMPANO BEACH		MUNICODE		SECTION 155.9402.C
EVERY PART OF EVERY REQUIRED YARD SHALL REMAIN OPEN AND UNOBTSTRUCTED FROM THE GROUND TO THE SKY EXCEPT AS OTHERWISE ALLOWED IN TABLE 155.9402.C. ALLOWABLE REQUIRED YARD ENCROACHMENTS, OR ALLOWED OR LIMITED BY PROVISIONS IN ARTICLE 4, USE STANDARDS, ARTICLE 5, DEVELOPMENT STANDARDS, OR ELSEWHERE IN THIS CODE.		OPEN BALCONIES		3 FEET
		MAX. 5 FEET		

4 PARKING AND LOADING REQUIREMENTS			
OFF-STREET PARKING SPACE DIMENSIONS			ALLOWED / REQUIRED
CITY OF POMPANO BEACH			MUNICODE
SECTION 155.5102.I.1 & 155.5102.I.2			STANDARD
SEE TABLE 155.5102.I.1: DIMENSIONAL STANDARDS FOR PARKING SPACES AND AISLES			9'-0" X 18'-0"
WHEN COMPACT PARKING SPACES PROVIDED IN A PARKING GARAGE, THE DIMENSIONS OF UP TO 20% OF THE REQUIRED OFF-STREET PARKING SPACES MAY BE REDUCED TO A WIDTH OF 8 FEET AND 4 INCHES AND A DEPTH/LENGTH OF 16 FEET. THE SPACES SHALL BE MARKED AS COMPACT PARKING SPACES.			ADA
			12'-0" X 18'-0"
			COMPACT
			8'-6" X 16'-0"

OFF-STREET LOADING SPACE DIMENSIONS			ALLOWED / REQUIRED
CITY OF POMPANO BEACH			MUNICODE
SECTION 155.5102.M.2			STANDARD
EACH LOADING BERTH SHALL BE OF SUFFICIENT SIZE TO ACCOMMODATE THE TYPES OF VEHICLES LIKELY TO USE THE LOADING AREA. THE MINIMUM LOADING BERTH SIZE THAT PRESUMPTIVELY SATISFIES LOADING BERTH NEEDS IS AT LEAST 12 FEET WIDE AND 55 FEET LONG. THE DEVELOPMENT SERVICES DIRECTOR MAY REQUIRE A LARGER LOADING BERTH OR ALLOW A SMALLER LOADING BERTH ON DETERMINING THAT THE CHARACTERISTICS OF THE PARTICULAR DEVELOPMENT WARRANT SUCH INCREASE OR REDUCTION AND THE GENERAL STANDARD IS MET.			WIDTH
			LENGTH
			VERTICAL CLEARANCE
			12'-0"
			55'-0"
			14'-0"

PARKING AISLES WIDTH			ALLOWED / REQUIRED
CITY OF POMPANO BEACH			MUNICODE
SECTION 155.5102.L.1			STANDARD
FOR ONE-WAY TRAFFIC, AISLES FOR TWO-WAY TRAFFIC SHALL BE AT LEAST 23 FEET WIDE (FOR ALL PARKING ANGLES). THE DEVELOPMENT SERVICES DIRECTOR MAY APPROVE AN AISLE WIDTH LESS THAN THE MINIMUM ON DETERMINING THAT THE AISLE IS SUFFICIENTLY WIDE TO ALLOW VEHICLE TO CONVENIENTLY MANUEVER THROUGH THE PARKING AREA AND ACCESS EACH PARKING SPACE WITHOUT DRIVING THROUGH ANY OTHER PARKING SPACE.			ONE-WAY
			23'-0"
			TWO-WAY
			23'-0"

DIVEWAY WIDTH			ALLOWED / REQUIRED
CITY OF POMPANO BEACH			MUNICODE
SECTION 155.5101.G.7.A			STANDARD
I. ONE-WAY DRIVEWAYS SHALL BE AT LEAST 22 FEET WIDE, AS MEASURED BETWEEN THE EDGES OF PAVING.			ONE-WAY
			12'-0"
II. TWO-WAY DRIVEWAYS SHALL BE AT LEAST 24 FEET WIDE, AS MEASURED BETWEEN THE EDGES OF PAVING.			TWO-WAY
			24'-0"

NUMBER OF REQUIRED PARKING SPACES - RESIDENTIAL			ALLOWED / REQUIRED
CITY OF POMPANO BEACH			MUNICODE
SECTION 155.5102.D.1			EFFICIENCY
			1.5 PS / DU = 88 DU = 132 PS
			1 BEDROOMS
			1.5 PS / DU = 34 DU = 51 PS
			2 BEDROOMS
			2 PS / DU = 10 DU = 20 PS
			TOTAL
			203 PS

NUMBER OF REQUIRED GUEST PARKING SPACES - RESIDENTIAL			ALLOWED / REQUIRED
CITY OF POMPANO BEACH			MUNICODE
ORDINANCE NO. 2023 - 72			STANDARD
			1 PS / 5 DU
			132 DU / 5 = 26.4
			ROUND UP TO 27 PS
3 PER 5 DU IN ADDITION TO THE REQUIRED PARKING SPACES BASED ON DWELLING UNIT			27 PS

NUMBER OF REQUIRED PARKING SPACES - COMMERCIAL			ALLOWED / REQUIRED
CITY OF POMPANO BEACH			MUNICODE
SECTION 155.5102.D.1			PROPOSED RETAIL
			1 PS / 300 GFA
			= 3,660 SF / 300 SF
			= 12.2 PS
			EXISTING BANK
			1 PS / 300 GFA
			= 3,250 SF / 300 SF
			= 10.8 PS
			EXISTING OFFICE
			1 PS / 400 GFA
			= 60,007 SF / 400 SF
			= 150.24 PS
			TOTAL
			175 PS

NUMBER OF REQUIRED PARKING SPACES WITH PARKING REDUCTION			ALLOWED / REQUIRED
CITY OF POMPANO BEACH			MUNICODE
SECTION 155.2421.B.1			PARKING REDUCTION
			MAJOR ADMINISTRATIVE ADJUSTMENT
			40% = 40% X 405 PS = 162 PS
			TOTAL PARKING REQUIRE WITH REDUCTION
			405 PS - 162 PS = 243 PS

NUMBER OF REQUIRED ADA PARKING SPACES			ALLOWED / REQUIRED
U.S. DEPARTMENT OF JUSTICE CIVIL RIGHTS DIVISION			2010 ADA STANDARDS FOR ACCESSIBLE DESIGN
TABLE 208.2 PARKING SPACES			TOTAL NUMBER OF PARKING SPACES PROVIDED IN A PARKING LOT OR FACILITY
			SPACES
			1 TO 25
			26 TO 50
			51 TO 75
			76 TO 100
			101 TO 150
			151 TO 200
			201 TO 300
			301 TO 400
			401 TO 500
			500 TO 1000
			1000 AND OVER
			20, PLUS 1 FOR EACH 100

NUMBER OF ALLOWED COMPACT PARKING SPACES (MAXIMUM)			ALLOWED / REQUIRED	PROVIDED
CITY OF POMPAÑO BEACH	MUNICODE	SECTION 155.5102.I.2	20% OF TOTAL REQUIRED PARKING SPACES 0.2 * 243 PS = 48 PS	46 SPACES, SEE FLOOR PLANS FOR LOCATION
WHEN COMPACT PARKING SPACES PROVIDED IN A PARKING GARAGE, THE DIMENSIONS OF UP TO 20% OF THE REQUIRED OFF-STREET PARKING SPACES MAY BE REDUCED TO A WIDTH OF 8 FEET AND 6 INCHES AND A DEPTH/LENGTH OF 16 FEET. THE SPACES SHALL BE MARKED AS COMPACT PARKING SPACES.				