


IRRIGATION HEAD LEGEND


IRRIGATION HEAD LEGEND						
SYMBOL QUANTITY	SYMBOL	DESCRIPTION	DETAIL DESIGN	DESIGN POST	DESIGN GPM PER SYMBOL	
116	☐	EACH SYMBOL DENOTES TWO (2) RAIN BIRD 1804-SAM-1401 FLOOD BUBBLERS	Q	30	0.50	
6	①	RAIN BIRD 1806-SAM-PRS-30 W/ HUNTER MPCORNER NOZZLE ADJ ARC 0-90	R	30	VAR	
73	②	RAIN BIRD 1806-SAM-PRS-30 W/ HUNTER MP1000 NOZZLE MAROON ADJ ARC 90-210	R	30	VAR	
3	③	RAIN BIRD 1806-SAM-PRS-30 W/ HUNTER MP1000 NOZZLE LIGHT BLUE ADJ ARC 210-270	R	30	VAR	
1	④	RAIN BIRD 1806-SAM-PRS-30 W/ HUNTER MP1000 NOZZLE OLIVE ADJ ARC 360	R	30	0.65	
45	⑤	RAIN BIRD 1806-SAM-PRS-30 W/ HUNTER MP2000 NOZZLE BLACK ADJ ARC 90-210	R	30	VAR	
1	⑥	RAIN BIRD 1806-SAM-PRS-30 W/ HUNTER MP2000 NOZZLE GREEN ADJ ARC 210-270	R	30	VAR	
1	⑦	RAIN BIRD 1806-SAM-PRS-30 W/ HUNTER MP2000 NOZZLE RED ARC 360	R	30	1.27	
11	⑧	RAIN BIRD 1806-SAM-PRS-30 W/ HUNTER MP3000 NOZZLE BLUE ADJ ARC 90-210	R	30	VAR	
1	⑨	RAIN BIRD 1806-SAM-PRS-30 W/ HUNTER MP3000 NOZZLE YELLOW ADJ ARC 210-270	R	30	VAR	
2	⑩	RAIN BIRD 1806-SAM-PRS-30 W/ HUNTER MP3000 NOZZLE GRAY ARC 360	R	30	3.15	
15	⑪	RAIN BIRD 1806-SAM-PRS-30 W/ HUNTER MP3500 NOZZLE LT. BROWN ADJ ARC 90-210	R	30	VAR	
7	⑫	RAIN BIRD 1806-SAM-PRS-30 W/ HUNTER MPCORNER NOZZLE RST	R	30	VAR	
5	⑬	RAIN BIRD 1806-SAM-PRS-30 W/ HUNTER MPCORNER NOZZLE LST	R	30	VAR	
49	⑭	RAIN BIRD 1806-SAM-PRS-30 W/ HUNTER MPCORNER NOZZLE SST	R	30	VAR	
4	⑮	RAIN BIRD 1806-SAM-PRS-30 W/ HUNTER MP800SR NOZZLE				

SYMBOL	MANUFACTURER/MODEL/DESCRIPTION	QTY		PSI		DETAIL
	AREA TO RECEIVE DRIPLINE NETAFIM TLHCVXR-CS-077-12 TECHLINE HCVXR-CS PRESSURE COMPENSATING LANDSCAPE DRIPLINE WITH COPPER STRIPE, CHECK VALVE AND ANTI-SIPHON FEATURE. 0.77 GPH EMITTERS AT 12" O.C. DRIPLINE LATERALS SPACED AT 12" APART, WITH EMITTERS OFFSET FOR TRIANGULAR PATTERN. 17MM.	8,144	LF	30		M,N

IRRIGATION LEGEND

IRRIGATION LEGEND			
QTY	SYM	DESCRIPTION	DET.
		STATION NUMBER	
		GALLONS PER MINUTE-CATALOG FLOW	
		VALVE SIZE	
1		LINE SIZE BY 2" TAP, MAXIMUM 10' OF 2" POLYETHYLENE SERVICE LINE AND A PROPOSED 1" POTABLE WATER METER (ALL BY OTHERS)	A
1		1" FEBCO 765 PRESSURE VACUUM BREAKER BACKFLOW ASSEMBLY	A
8		RAIN BIRD PEB SERIES REMOTE CONTROL VALVE (SIZED PER PLAN) WITH A NIBCO T-113 GATE VALVE IN A CARSON 1220 JUMBO VALVE BOX WITH BOLT DOWN LID	B
3		RAIN BIRD PEB SERIES REMOTE CONTROL VALVE WITH A SENNINGER PRESSURE REGULATOR (BASED ON FLOW**), NIBCO T-113 GATE VALVE AND NETAFIM MANUAL DISC FILTER MODEL DF100-140, EACH IN A SEPARATE CARSON 1220 JUMBO VALVE BOX WITH BOLT DOWN LID	B1 B2
1		RAIN BIRD ESP-LXME WALL MOUNT 12 STATION CONTROLLER, GROUNDING GRID AND BASELINE WATERTEC S100 SOIL MOISTURE SENSOR INTERFACE MOUNTED ADJACENT TO CONTROLLER	C1
1		EAVE MOUNTED HUNTER RAIN FREEZE CLIK SENSOR MODEL RFC, WIRE TO BE CONNECTED TO CONTROLLER VIA 1" CONDUIT	C2
1		BASELINE WATERTEC S100 SOIL MOISTURE SENSOR bSENSOR INSTALLED ON SITE PER MANUFACTURER'S RECOMMENDATIONS. COMMUNICATION WIRE TO BE CONNECTED TO SMS INTERFACE AT CONTROLLER VIA 1" CONDUIT	C3
3		NIBCO T-113 BRONZE MAINLINE ISOLATION VALVE (LINE SIZE) IN A CARSON 1419 VALVE BOX.	D
		CLASS 200 PVC LATERAL LINE W/ SCH 40 SOLVENT WELD PVC FITTINGS (SIZE PER PLAN, MINIMUM PIPE SIZE SHALL BE 3/4", NO 1/2" PIPES PERMITTED)	L
		SCHEDULE 40 SOLVENT-WELD PVC MAINLINE W/SCH 40 SOLVENT-WELD PVC FITTINGS (SIZE PER PLAN)	L
		SCH 40 GRAY PVC ELECTRICAL CONDUIT, WITH SCH 40 PVC FITTINGS (SIZE PER PLAN)	L
		NETAFIM TLHCVR7-CS-12, PRESSURE COMPENSATING LANDSCAPE DRILLING WITH COPPER STRIPE, CHECK VALVE, ANTI-SIPHON FEATURE AND 0.77 GPH EMITTERS AT 12" O.C. SPACING. DRIPLINE LATERALS SPACED AT 12" APART, WITH EMITTERS OFFSET FOR TRIANGULAR GRID EMITTER PATTERN. DRIP ZONES INSTALLED WITH DRIP OPERATION INDICATORS. REFER TO PLAN DETAILS	M,N
		CLASS 200 PVC HEADER W/SCH 40 SOLVENT-WELD PVC FITTINGS (SIZE PER PLAN)	M,N
		CLASS 200 PVC SLEEVES W/SCH 40 SOLVENT-WELD PVC FITTINGS (SIZE PER PLAN) NOTE: EVERY MAINLINE SLEEVE/SLEEVE LOCATION SHALL BE ACCOMPANIED BY AN ADDITIONAL 2" SLEEVE FOR IRRIGATION CONTROL WIRES	O
QUANTITIES GIVEN ARE FOR CONTRACTOR CONVENIENCE ONLY. THE ACCURACY IS NOT GUARANTEED. ALL QUANTITIES SHALL BE VERIFIED.			
*DET. (ON THE LEGEND) - THE LETTER IN THIS COLUMN DENOTES THE CORRESPONDING DETAIL SHOWN ON THE DETAIL SHEET.			
** SENNINGER PRESSURE REGULATORS (INLET NPT X OUTLET NPT): PRL30: 0.5-8.0 GPM (3/4"x3/4") PRHF: 10.0-32.0 GPM (1-1/4"x1, 1-1/4") PRU: 20-100 GPM (2"x2")			

						DATE	5/1/25
						SCALE:	AS SHOWN
						DESIGN BY:	TFP
						DRAWN BY:	TFP
						CHECKED BY:	MOMMY
						APPROVED BY:	MW
						BY:	DATE
						DESCRIPTION	

 **Craven & Thompson & Associates, Inc.**
ENGINEERS • PLANNERS • SURVEYORS
3563 N.W. 53RD STREET, FORT LAUDERDALE, FLORIDA 33309
TEL: (954) 739-6409
FAX: (954) 739-6408
FLORIDA LICENSED ENGINEERING, SURVEYING & MAPPING BUSINESS NO. 271
FLORIDA LICENSED LANDSCAPE ARCHITECTURE BUSINESS NO. C000114

MATERIAL SUPPLY METHOD IS THE PROPERTY OF CRAVEN & THOMPSON & ASSOCIATES, INC. AND SHALL NOT BE REPRODUCED IN WHOLE OR IN PART WITHOUT WRITTEN PERMISSION OF CRAVEN & THOMPSON & ASSOCIATES.

ATLANTIC FLEET WASH
1501 WEST ATLANTIC BLVD.
POMPANO BEACH, FLORIDA

PREPARED FOR:
KAJA PROPERTIES INC.

IRRIGATION LEGENDS

Nicole D. Pastre
Florida R.L.A. No. 6667397
2025-05-27

PROJECT NO.
24-0055-001-01

IR-1

SHEET 1 OF 6



PZ24-12000026

08.20.2025

