



DRC

PZ24-12000024

Date	Description	No.
07/02/2025		

REVISIONS

★

MICHAEL P. CARR

★

LICENSE

No. 72424

★

STATE OF

FLORIDA

★

SIGNATURE

ENGINEER

DATE SIGNED

MICHAEL CARR

PROFESSIONAL ENGINEER FL Lic. No. 72424

LANGAN

Langan Engineering and Environmental Services, LLC

110 East Broward Boulevard, Suite 1500

Fort Lauderdale, FL 33301

T: 954.320.2100 F: 954.320.2101 www.langan.com

FL CERTIFICATE OF AUTHORIZATION NO. 00006601/LB8172/LB8198

FESTIVAL INDUSTRIAL

POMPAN0 BEACH
BROWARD COUNTY FLORIDA

PAVEMENT PLAN

Project No.	Drawing No.
330134201	C-3.0
Date	
FEBRUARY 2025	
Drawn By	
EWM	
Checked By	
MPC	

CONCRETE SIDEWALK

①

②

③

LIGHT DUTY ASPHALT

1. 1.5" FC-9.5 OR FC-12.5 SURFACE COURSE

2. 6" LIMEROCK BASE MIN. LBR 100, COMPACTED 98% MAX. DENSITY PER AASHTO T-180

3. 12" STABILIZED SUBGRADE MIN. LBR 40, COMPACTED TO 98% MAX. DENSITY PER AASHTO T-180

①

②

③

HEAVY DUTY ASPHALT

1. 2" FC-9.5 OR FC-12.5 SURFACE COURSE

2. 8" LIMEROCK BASE MIN. LBR 100, COMPACTED 98% MAX. DENSITY PER AASHTO T-180

3. 12" STABILIZED SUBGRADE MIN. LBR 40, COMPACTED TO 98% MAX. DENSITY PER AASHTO T-180

①

②

③

HEAVY DUTY CONCRETE PAVEMENT

1. 6" 3,000 PSI CONCRETE REINFORCED WITH #3 BAR @16" ON-CENTER EACH WAY AND WITH SYNTHETIC MICROFIBERS @ 7.5 LBS/CY

2. 6" LIMEROCK BASE MIN. LBR 100, COMPACTED 98% MAX. DENSITY PER AASHTO T-180

3. 12" STABILIZED SUBGRADE MIN. LBR 40, COMPACTED TO 98% MAX. DENSITY PER AASHTO T-180

①

②

③

CONCRETE PAVEMENT (SIDEWALK)

1. 6" 3,000 PSI CONCRETE REINFORCED WITH #3 BAR @16" ON-CENTER EACH WAY AND WITH SYNTHETIC MICROFIBERS @ 7.5 LBS/CY

2. 8" LIMEROCK BASE MIN. LBR 100, COMPACTED 98% MAX. DENSITY PER AASHTO T-180

3. 12" STABILIZED SUBGRADE MIN. LBR 40, COMPACTED TO 98% MAX. DENSITY PER AASHTO T-180

LIGHT DUTY ASPHALT PAVEMENT

HEAVY DUTY ASPHALT PAVEMENT

HEAVY DUTY CONCRETE PAVEMENT

CONCRETE PAVEMENT