



NOTES:
ALL TYPE "F" CURB & GUTTER SHALL BE IN ACCORDANCE WITH THE STANDARD REQUIREMENTS OF FDOT INDEX 520-001.

"WHEN USED ON HIGH SIDE OF ROADWAYS, THE CROSS SLOPE OF THE GUTTER SHALL MATCH THE CROSS SLOPE OF THE ADJACENT PAVEMENT. THE THICKNESS OF THE LIP SHALL BE 6", UNLESS OTHERWISE SHOWN ON PLANS.

The diagram illustrates the cross-section of a Type 'F' curb and gutter assembly. The curb lip has a height of 6 inches and a top width of 1 foot 6 inches. The outer face of the curb features a 2-inch radius (2" R) at the top edge and a 3-inch radius (3" R) at the bottom edge. The gutter opening is 7.5 inches wide at its base, with a standard depth of 6 inches minimum (STD. 6" MIN.). The gutter is filled with asphalt, which sits atop a limerock base layer that is 8 inches thick. Below the limerock base is the subgrade. A vertical dimension of 6 inches is shown from the top of the curb lip down to the top of the limerock base. Labels include: CONC. CURB & GUTTER, ASPHALT, LIMEROCK BASE, SUBGRADE, and STD. 6" MIN. 7.5".

TYPE "F" CURB DETAIL
PER FDOT INDEX No. 520-001

7

NOT TO SCALE

