

1 FLOOR PLAN - LEVEL 1
1/8" = 1'-0"

FLOOR PLAN GENERAL NOTES

- REFER TO A120 FOR FINISH SCHEDULES.
- REFER TO SHEETS A802 - A802 FOR DOOR SCHEDULE.
- REFER TO SHEETS A910 - A914 FOR PARTITION, WALL TYPES AND TYP. DETAILS.
- REFER TO ENLARGED PLANS FOR ADDITIONAL DETAILS AND SECTIONS.
- REFER TO STRUCTURAL DRAWINGS FOR ALL CONCRETE WALLS, SLAB DEPRESSION LOCATIONS AND DEPTHS.
- LEVEL 1 FLOOR ELEVATION 14'-0" EQUALS NAVD 88. REFER TO CIVIL FOR ALL SITE GRADE ELEVATIONS.
- ALL PARTITIONS ARE DIMENSIONED FROM FACE OF FINISH TO FACE OF FINISH OR COLUMN LINE TO FACE OF FINISH. UON. DIMENSION NOTED BY CENTERLINE SYMBOL. REFER TO CENTERLINE OF PARTITION.
- ALL DIMENSIONS MARKED "CLEAR" OR "HOLD" SHALL BE MAINTAINED AND SHALL ALLOW FOR THICKNESS OF ALL WALL FINISHES.
- CONTRACTOR TO VERIFY ALL CONDITIONS AND PLAN DIMENSIONS PRIOR TO BEGINNING ANY CONSTRUCTION OR FABRICATION, AND NOTIFY ARCHITECT IN WRITING OF ANY DISCREPANCIES.
- WHERE FURRED PARTITIONS EXCEED MAX. HEIGHT, BRACE TO ADJACENT STRUCTURE.
- ALL EXTERIOR CMU WALLS TO BE INSTALLED UP TO BOTTOM OF STRUCTURE. ALLOW FOR LIVE LOAD DEFLECTION OF STRUCTURE ABOVE PER STRUCTURAL. REFER TO PARTITION TYPES AND MODIFIERS FOR THERMAL AND FIRE RATING. ALL CMU WALLS ARE TO BE BRACED TO STRUCTURE PER STRUCTURAL ENGINEERS DOCUMENTS.
- ALL DOORS TO BE 4" FROM FACE OF ADJACENT FINISHED PERPENDICULAR WALL TO EDGE OF DOOR. UON.
- PROVIDE FIRE RATED EXTINGUISHER CABINET WHERE LOCATED IN RATED PARTITION.
- PROVIDE CONCRETE PADS FOR ALL AHUS, CHILLERS PUMPS, GENERATORS, FUEL TANKS PER MEP DRAWINGS AND MANUFACTURER CRITERIA. REFER TO STRUCTURAL DRAWINGS FOR DETAILS.
- ALL CONCRETE PADS TO BE COORDINATED WITH ELECTRICAL EQUIPMENT MANUFACTURER. DIMENSIONS TO BE USED AS REFERENCE ONLY.
- EE FINISH PLANS FOR FINISHES, FLOORING PATTERNING, MILLWORK ENLARGEMENT REFERENCES AND FLOOR TRANSITIONS. (TO BE ISSUED IN DD)
- SEE INTERIOR FURNITURE DRAWINGS FOR ADDITIONAL INFORMATION FOR FURNITURE AND EQUIPMENT. (TO BE ISSUED IN DD)
- CONTRACTOR TO PROVIDE SUPPORT/BRACING FOR ALL SIGNAGE AND EQUIPMENT AS REQUIRED TO PROVIDE ADEQUATE SUPPORT. SIGNAGE AND EQUIPMENT LOCATION AND WEIGHTS SHALL BE COORDINATED WITH SUPPLIER/OWNER AND SHOWN AS APPLICABLE ON REQUIRED SHOP DRAWINGS.
- ALL PLYWOOD AND WOOD JOINTS SHALL BE FIRE RESISTANT.
- ALL GYPSUM BOARD WALLS AND FURRING SHOULD COMPLETELY COVER ALL COLUMNS, FIRE PROOFING, SHEARWALLS AND CONCRETE BLOCK WALLS WITHOUT BUMP-OUTS OR MISALIGNMENTS. FACE OF ALL WALLS TO ALIGN. CONTACT ARCHITECTS IMMEDIATELY IF DURING THE LAYOUT PHASE OF THE WALL CONSTRUCTION THIS IS FOUND NOT TO BE THE CASE.
- PROVIDE WATER RESISTANT GYPSUM BOARD AT ALL MOISTURE LOCATIONS. PROVIDE CEMENTITIOUS BOARD AT ALL WET LOCATIONS.
- ALL PARTITIONS TO BE TYPE "A" WITH SAFB UNLESS NOTED OTHERWISE.
- REFER TO LIFE SAFETY DRAWINGS (G-SERIES) FOR FIRE EXTINGUISHER TYPES & LOCATIONS. (TO BE ISSUED IN DD)
- WHERE MILLWORK IS PRESENT AND ADJACENT TO A WALL, PROVIDE 16 GAUGE METAL STUD REINFORCEMENT AT CANTILEVERED COUNTER CONDITION. REFER TO DETAIL A9H.

FLOOR PLAN LEGEND

- NEW PARTITION AS INDICATED, TERMINATE IF ABOVE FINISH CEILING
- NEW GLAZED OPENING WITH ALUM OR RM FRAME AS INDICATED. AT COUNTERS PROVIDE HEADR CONTINUOUS TO UNDERSIDE OF SLAB ABOVE.
- DOOR OPENING TYPE
- NEW CASINGWORK. COORDINATE WITH POWER AND DATA
- ACoustical PARTITION. PROVIDE FULL HEIGHT. FINISH SAFB. (TYPE TO BE DETERMINED BY DESIGN/CONSTRUCTION). AT SLAB DECK, PROVIDE DOUBLE GLAZING
- PROVIDE FULL HEIGHT PARTITION ADJACENT TO OPEN OFFICE AREA

PZB
P226-12000002
05/27/2026