



Heilmuth, Obata & Kassabaum, Inc.
124 Giraldade Avenue, Suite 100
Coral Gables, FL 33134 USA
t +1 786 539 0800
www.hok.com/studios/miami

Qualifying Agent, Jonathan Rae - FL Reg. No. AR02342

All reproduction & related property rights reserved © 2025
In Association with



THA Consulting, Inc.
Pompano
40 NW 3rd Street, Suite 1102
Miami, FL 33128
T: 305 582 7123
www.tha-consulting.com



Hammond & Associates Inc.
Mechanical, Fire Protection
489 N. 7th Ave, Suite 215
Pompano, FL 33077
PH: 564 327 7111
www.hammondengineers.com



Kugler Ning Lighting, Inc.
Lighting design
247 West 27th Street Suite 1502
New York, NY 10018
www.kuglerning.com



SOCOTEC Life Safety, LLC
Life Safety
1380 W. Peachtree St NW Suite #1010
Atlanta, GA 30309
www.socotec.us



VDA, Inc.
Vertical Transportation
1000 West McAlister Road, Suite 209
Pompano Beach, FL 33069



Brooks Acoustics
Acoustics
48 N. Federal Highway, #121
Pompano Beach, FL 33062



NOT FOR
CONSTRUCTION

Professional Seal



No.	Description	Date
1	50% SCHEMATIC DESIGN	10/10/2025
2	100% SCHEMATIC DESIGN	11/21/2025
3	10% DESIGN DEVELOPMENT	11/22/2025
4	100% DESIGN DEVELOPMENT	03/06/2026
5	CRG SUBMISSION	03/11/2026

1 FLOOR PLAN - LEVEL 3

1/8" = 1'-0"

FLOOR PLAN GENERAL NOTES

- REFER TO A120 FOR FINISH SCHEDULES.
- REFER TO SHEETS A802 - A820 FOR DOOR SCHEDULE.
- REFER TO SHEETS A910 - A914 FOR PARTITION, WALL TYPES AND TYP. DETAILS.
- REFER TO ENLARGED PLANS FOR ADDITIONAL DETAILS AND SECTIONS.
- REFER TO STRUCTURAL DRAWINGS FOR ALL CONCRETE WALLS, SLAB DEPRESSION LOCATIONS AND DEPTHS.
- LEVEL 1 FLOOR ELEVATION 14'-0" EQUALS NAVD 88. REFER TO CIVIL FOR ALL SITE GRADE ELEVATIONS.
- ALL PARTITIONS ARE DIMENSIONED FROM FACE OF FINISH TO FACE OF FINISH OR COLUMN LINE TO FACE OF FINISH. UON. DIMENSION NOTED BY CENTERLINE SYMBOL. REFER TO CENTERLINE OF PARTITION.
- ALL DIMENSIONS MARKED "CLEAR" OR "HOLD" SHALL BE MAINTAINED AND SHALL ALLOW FOR THICKNESS OF ALL WALL FINISHES.
- CONTRACTOR TO VERIFY ALL CONDITIONS AND PLAN DIMENSIONS PRIOR TO BEGINNING ANY CONSTRUCTION OR FABRICATION, AND NOTIFY ARCHITECT IN WRITING OF ANY DISCREPANCIES.
- WHERE FURRED PARTITIONS EXCEED MAX. HEIGHT, BRACE TO ADJACENT STRUCTURE.
- ALL EXTERIOR CMU WALLS TO BE INSTALLED UP TO BOTTOM OF STRUCTURE. ALLOW FOR LIVE LOAD DEFLECTION OF STRUCTURE ABOVE PER STRUCTURAL. REFER TO PARTITION TYPES AND MODIFIERS FOR THERMAL AND FIRE RATING. ALL CMU WALLS ARE TO BE BRACED TO STRUCTURE PER STRUCTURAL ENGINEERS DOCUMENTS.
- ALL DOORS TO BE 4" FROM FACE OF ADJACENT FINISHED PERPENDICULAR WALL TO EDGE OF DOOR. UON.
- PROVIDE FIRE RATED EXTINGUISHER CABINET WHERE LOCATED IN RATED PARTITION.
- PROVIDE CONCRETE PADS FOR ALL AHUS, CHILLERS PUMPS, GENERATORS, FUEL TANKS PER MEP DRAWINGS AND MANUFACTURER CRITERIA. REFER TO STRUCTURAL DRAWINGS FOR DETAILS.
- ALL CONCRETE PADS TO BE COORDINATED WITH ELECTRICAL EQUIPMENT MANUFACTURER. DIMENSIONS TO BE USED AS REFERENCE ONLY.
- EE FINISH PLANS FOR FINISHES, FLOORING PATTERNING, MILLWORK ENLARGEMENT REFERENCES AND FLOOR TRANSITIONS. (TO BE ISSUED IN DD)
- SEE INTERIOR FURNITURE DRAWINGS FOR ADDITIONAL INFORMATION FOR FURNITURE AND EQUIPMENT. (TO BE ISSUED IN DD)
- CONTRACTOR TO PROVIDE SUPPORT/BRACING FOR ALL SIGNAGE AND EQUIPMENT AS REQUIRED TO PROVIDE ADEQUATE SUPPORT. SIGNAGE AND EQUIPMENT LOCATION AND WEIGHTS SHALL BE COORDINATED WITH SUPPLIER/OWNER AND SHOWN AS APPLICABLE ON REQUIRED SHOP DRAWINGS.
- ALL PLYWOOD AND WOOD BLOCKING SHALL BE FIRE RESISTANT.
- ALL GYPSUM BOARD WALLS AND FURRING SHOULD COMPLETELY COVER ALL COLUMNS, FIRE PROOFING, SHEARWALLS AND CONCRETE BLOCK WALLS WITHOUT BUMP-OUTS OR MISALIGNMENTS. FACE OF ALL WALLS.
- CONTACT ARCHITECTS IMMEDIATELY IF DURING THE LAYOUT PHASE OF THE WALL CONSTRUCTION THIS IS FOUND NOT TO BE THE CASE.
- PROVIDE WATER RESISTANT GYPSUM BOARD AT ALL MOISTURE LOCATIONS. PROVIDE CEMENTITIOUS BOARD AT ALL WET LOCATIONS.
- ALL PARTITIONS TO BE TYPE "A" WITH SAF8 UNLESS NOTED OTHERWISE.
- REFER TO LIFE SAFETY DRAWINGS (G-SERIES) FOR FIRE EXTINGUISHER TYPES & LOCATIONS. (TO BE ISSUED IN DD)
- WHERE MILLWORK IS PRESENT AND ADJACENT TO A WALL, PROVIDE 16 GAUGE METAL STUD REINFORCEMENT AT CANTILEVERED COUNTER CONDITION. REFER TO DETAIL A44.

FLOOR PLAN LEGEND

- NEW PARTITION AS INDICATED, TERMINATE 6" ABOVE FINISH CEILING
- NEW GLAZED OPENING WITH ALUM OR RM FRAME AS INDICATED. AT CORNERS PROVIDE HEADER CONTINUOUS TO UNDERSIDE OF SLAB ABOVE.
- DOOR OPENING TYPE
- NEW CASINGWORK WITH COORDINATED WITH POWER AND DATA
- ACOUSTICAL PARTITION. PROVIDE FULL HEIGHT WITH SAF8 (TYPE TO BE DETERMINED BY DESIGN/ENLARGEMENT). AT GLASS DEMONSTRATION PROVIDE DOUBLE GLAZING
- PROVIDE FULL HEIGHT PARTITION ADJACENT TO OPEN OFFICE AREA

P226-12000002
05/27/2026

FLOOR PLAN - LEVEL 3

Original in 1/8" = 1'-0" scale contents of this drawing
Sheet Number

A103