

EXTERIOR ASSEMBLIES	
TYPE	DESCRIPTION
EXT-F1	CONCRETE SLAB ON GRADE. CONCRETE SLAB REFER TO STRUCTURAL. W/6" VAPOR BARRIER.
EXT-F2	KNEE ROOF INSULATION (HIGH ROOF) ROOF: INSULATED ROOF. EXTERIOR COVERBOARD SHEATHING, INSIC24" 2" MIN. (R20 MIN.) VAPOR BARRIER, 1/2" MIN. (R10 MIN.)
EXT-R1	PAVER ASSEMBLY AT MENITY TERRACE. PAV/01 PAVER TILES, R32/24 MM ECHO ROOF SYSTEM, 2PLY CLD FLUOROPOLYMER MEMBRANE, 1/2" EXTERIOR CEMENT BOARD SHEATHING, INSIC10 TAPERED ROOF INSULATION - 4" MIN AT LOW SLOPE (R20 MIN.) VAPOR BARRIER, 1/2" MIN. (R10 MIN.)
EXT-R2	PLANTING ASSEMBLY AT CEMENTY TERRACE. PLANTING MEDIA, R30/24 MM ECHO ROOF SYSTEM, 2PLY CLD APPLIED ROOF MEMBRANE, INSIC10 TAPERED ROOF INSULATION - 4" MIN AT LOW SLOPE (R20 MIN.)
EXT-R4	STANDING SEAM ROOF ASSEMBLY: LOW ROOF: R5/4" STANDING SEAM ROOF, SELF-ADHERING UNDERLAYMENT, 5/8" GALV. STEEL ROOFING, 1/2" EXTERIOR CEMENT BOARD SHEATHING, INSIC10 TAPERED ROOF INSULATION - 4" MIN AT LOW SLOPE (R20 MIN.) VAPOR BARRIER, 1/2" MIN. (R10 MIN.)
EXT-S1	VENTILATED SPOKE INSULATION (TYPICAL), MTP/03 LONGBOARD V GIRDERS w/ PERFORATED METAL SHEET, 3/8" CFM
EXT-W1	TYPICAL CURTAIN WALL - STANDARD GLAZING: EX/001 TYPICAL MILLION (S WINDOWS W/70/00), G1 GLAZING (BLUE, G1/2 SPANDREL, INS-03A MINERAL WOOL INSULATION BOARD)
EXT-W1A	TYPICAL CURTAIN WALL - STANDARD GLAZING: EX/001 TYPICAL MILLION (S WINDOWS W/70/00), G1/1 GLAZING (BLUE, G1/2 SPANDREL, INS-03A MINERAL WOOL INSULATION BOARD)
EXT-W2	TYPICAL CURTAIN WALL - CARVE: GLAZING: EX/001 TYPICAL MILLION (S WINDOWS W/70/00), G1/2 GLAZING (CLEAR, G1/2 SPANDREL, INS-03A MINERAL WOOL INSULATION BOARD)
EXT-W3	MONUMENTAL GLAZING: EX/005 GLASS FIN MILLION (LONG SPANDREL), G1/0 LONG SPANDREL GLAZING (ULTRA CLEAR, G1/2 SPANDREL, INS-03A MINERAL WOOL INSULATION BOARD)
EXT-W4	GFRC ON CMU - INSULATED (SERVICE VARIO): EX/001 SIMPSPEC, 12" 4" VERTICAL, RUNNING BOARD, 2 CHANNEL (VERTICAL), 2 CHANNEL (VERTICAL), 1/2" HIBRO COMPOSITE METAL GIRD (HORIZONTAL), INS/24 2" MINERAL WOOL INSULATION BOARD - CONTINUOUS (R3 MIN.) FLUIDAPPLIED BARBER, CMU/01 CMU
EXT-W6	SCALLOPED GFRC ON CMU - INSULATED (CHAMBERS): FRC/01 SCALLOPED GFRC 3 PANEL WIDTH 5/8" VERTICAL, 2 CHANNEL (VERTICAL), 1/2" HIBRO COMPOSITE METAL GIRD (HORIZONTAL), INS/24 2" MINERAL WOOL INSULATION BOARD - CONTINUOUS (R3 MIN.) FLUIDAPPLIED BARBER, CMU/01 CMU, INS/26 2 1/2" MINERAL WOOL BATT INSULATION (R3 MINIMUM)
EXT-W7	GFRC ON CMU - UNINSULATED (EXTERIOR STAIR, FRC/01 SCALLOPED GFRC 3 PANEL WIDTH 5/8" VERTICAL, 2 CHANNEL (VERTICAL), 1/2" HIBRO COMPOSITE METAL GIRD (HORIZONTAL), INS/24 2" MINERAL WOOL INSULATION BOARD - CONTINUOUS (R3 MIN.) FLUIDAPPLIED BARBER, CMU/01 CMU, INS/26 2 1/2" MINERAL WOOL BATT INSULATION (R3 MINIMUM)

