



CONCRETE DRIVEWAY  
RESTORATION (TYPE V)

## SURFACE RESTORATION

**PZ25- 12000016**  
**12/03/2025**



## SURFACE RESTORATION

A cross-sectional diagram of a trench repair. The diagram shows a central 'ASPHALT PAVEMENT PATCH' with a width labeled 'W' and '5'-0" MIN.'. The patch is 12" MIN. wide on the left side. Below the patch is a 'NEW BASE (MIN. 12" THICKNESS) (MAX. 18" THICKNESS)'. The existing base is shown on the right. The trench is filled with 'TRENCH BACKFILL AS APPLICABLE'. A 'TACK COAT BETWEEN EXISTING AND NEW SURFACES' is indicated on the left. A 'MECHANICALLY SAW CUT JOINTS' is indicated on the right. The diagram also shows 'EXISTING PAVEMENT' on the left and 'TRENCH' at the bottom.

PERPENDICULAR ROAD  
CROSSINGS (TYPE III)

## SURFACE RESTORATION

ENGINEERING STANDARDS 2022			
REVISIONS		ENGINEERING DIVISION CITY OF POMPANO BEACH	SURFACE RESTORATION
BY	DATE		
		SCALE: N.T.S.	DATE: MAY 2022 DWG. NO. 306-2