



WALL LEGEND

- TYPICAL 8" CMU WALL
- TYPICAL 8" CMU WALL - FIRE RATED
- TYPICAL 5" INTERIOR PARTITION NON RATED - GYP. ON BOTH SIDES

FLOOR LEGEND

- Proposed Finish Floor Elevation - FFE
- Step

SUSTAINABLE STANDARDS

EFFICIENT COOLING - 2 POINTS
ALL AIR CONDITIONING UNITS SHALL BE ENERGY STAR® QUALIFIED.

EFFICIENT WATER HEATING - 2 POINTS
A MINIMUM OF 75% OF THE DOMESTIC HOT WATER ON-SITE SHALL BE PROVIDED BY TANKLESS OR SOLAR WATER HEATING SYSTEMS.

HURRICANE RESISTANT STRUCTURES - 4 POINTS
THE PRINCIPAL BUILDING SHALL BE DESIGNED TO MEET ENHANCED WIND-LOAD REQUIREMENTS FOR A MINIMUM WIND SPEED OF 150 MPH.

PARKING STRUCTURE - 2 POINTS
AT LEAST 75% OF THE REQUIRED OFF-STREET PARKING SPACES SHALL BE LOCATED WITHIN ENCLOSED GARAGES, MEETING THE CRITERIA FOR STRUCTURED PARKING.