

Materials: Steel (Stainless steel available)

Standard Finish: Plain or Electro-Plated

Service: Designed for supporting vertical or horizontal pipe runs at a fixed distance from a wall or structure.

Ordering: Specify part number and finish.

Note: Ductile and cast iron sizes are available.

Design Load

Part No.	Pipe Size In. (mm)	A In. (mm)		C In. (mm)		H In. (mm)	Design Load Lbs. (kN)		Approx. Wt./100 Lbs. (kg)
		In.	mm	In.	mm		Lbs.	kN	
B3108-1/8	1/8" (12.7)	2 1/8"	53.9	3/8"	9.5	3/8"	170	184	107 (48.5)
B3108-3/4	3/4" (19.0)	2 1/2"	63.5	3/8"	9.5	3/8"	190	194	109 (49.4)
B3108-1	1" (25.4)	2 3/8"	60.3	3/8"	9.5	3/8"	190	194	116 (52.8)
B3108-1 1/4	1 1/4" (32.1)	2 3/8"	60.3	3/8"	9.5	3/8"	190	194	126 (57.1)
B3108-1 1/2	1 1/2" (40)	3"	76.2	3/8"	9.5	3/8"	190	194	134 (60.8)
B3108-2	2" (50.8)	3 3/8"	81.3	3/8"	9.5	3/8"	420	187	191 (86.6)
B3108-2 1/2	2 1/2" (63.5)	3 3/8"	81.3	3/8"	9.5	3/8"	420	187	209 (94.8)
B3108-3	3" (76.2)	3 3/4"	95.2	3/8"	9.5	3/8"	420	187	232 (105.3)
B3108-3 1/2	3 1/2" (90)	4"	101.6	3/8"	9.5	3/8"	420	187	255 (115.6)
B3108-4	4" (101.6)	4 1/4"	108.0	3/8"	9.5	3/8"	420	187	270 (122.5)
B3108-5	5" (127)	5" (127)	127.0	1/2"	12.7	1/2"	1430	807	690 (314.0)
B3108-6	6" (152.4)	6" (152.4)	152.4	1/2"	12.7	1/2"	1430	807	787 (357.0)
B3108-8	8" (203.2)	8" (203.2)	203.2	1/2"	12.7	1/2"	2680	1203	1451 (660.5)
B3108-12	12" (304.8)	12" (304.8)	304.8	1/2"	12.7	1/2"	2680	1203	2100 (952.5)

Materials: Steel (Stainless steel available)

Standard Finish: Plain or Electro-Plated

Service: Designed for suspending pipe runs where exact distance from structure to pipe cannot be determined until installation. Field modify legs to suit conditions.

Ordering: Specify part number and finish.

Note: Ductile and cast iron sizes are available.

CONCRETE SADDLE

NOTE:

ALL DETAILS SHOWN FOR EXAMPLE ONLY. DESIGNER SHALL ASSUME RESPONSIBILITY FOR COMPLETE AND ADEQUATE DESIGN OF ALL COMPONENTS.

