

STORMWATER MANAGEMENT CALCULATIONS

PZ23-12000046

04/03/2024

I. GIVEN:**A. POST DEVELOPMENT ACREAGE:**

1. Buildings = 0.000 ac.
2. Total Impervious = 0.090 ac.
3. Pervious = 0.010 ac.
4. Dry Retention Area = 0.000 ac.
4. Total Site Area = 0.100 ac.

B. ZONING:

1. Commercial

This item has been digitally signed and sealed by Justin Thompson, PE, on the date adjacent to the seal.

Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.



02/29/2024

II. DESIGN CRITERIA:**A. WATER QUALITY CRITERIA:**

1. If a wet detention system, then whichever is the greater of the following:
 - a. The first inch of runoff from the entire project site.
 - b. The amount of 2.5 inches times the percent impervious for the project site.
2. If a dry detention system, then 75% of the volume required for the wet detention system.
3. If a retention system, then 50% of the volume required.
4. If the property is zoned "Commercial", at least 1/2 inch of retention or dry detention pre-treatment will be required.
5. Any detention system shall be designed to discharge no more than 0.5 inches of the detained volume per day.

III. COMPUTATIONS**A. WATER QUALITY COMPUTATIONS:**

1. Compute the first inch of runoff from the entire developed project site:

$$= 1.00 \text{ inch} \times 0.100 \text{ acres} \times (1 \text{ foot} / 12 \text{ inches})$$

$$= \boxed{0.008} \text{ ac-ft for the first inch of runoff}$$
2. Compute 2.5 inches times the percent impervious for the developed project site:
 - a. Site area for water quality pervious / impervious calculations only:

$$= \text{Total Project Area} - (\text{Water / Retention Area} + \text{Buildings})$$

$$= 0.100 \text{ acres} - (0.000 \text{ acres} + 0.000 \text{ acres})$$

PZ23-120000 **0.100** acres of site area for water quality calculations

04/03/2024

b. Impervious area for water quality pervious / impervious calculations only:

$$= \text{Site area for water quality} - \text{Pervious area}$$

$$= 0.100 \text{ acres} - 0.010 \text{ acres}$$

$$= \mathbf{0.090} \text{ acres of impervious area for water quality calculations}$$

c. Percentage of impervious area for water quality:

$$= \text{Impervious area for water quality} / \text{Site area for water quality} \times 100\%$$

$$= 0.090 \text{ acres} / 0.100 \text{ acres} \times 100\%$$

$$= \mathbf{90.0\%} \text{ Impervious}$$

d. For 2.5 inches times the percentage of impervious area:

$$= 2.5 \text{ inches} \times 90.0\%$$

$$= \mathbf{2.250} \text{ inches to be treated}$$

e. Compute volume required for quality:

$$= \text{Inches to be treated} \times (\text{Total Site Area} - \text{Water} / \text{Retention Area})$$

$$= 2.250 \text{ inches} \times (0.100 \text{ acres} - 0.000 \text{ acres}) \times (1 \text{ foot} / 12 \text{ inches})$$

$$= \mathbf{0.019} \text{ ac-ft required for detention storage}$$

3. → The first inch of runoff from the entire developed site =

$$\mathbf{0.008} \text{ ac-ft}$$

→ 2.5 inches times the percentage of impervious area =

$$\mathbf{0.019} \text{ ac-ft}$$

→ Volume of **0.019** ac-ft controls

4. If the project is zoned "Commercial" or if the project were discharging directly to a sensitive receiving body and is more than 40% impervious, 0.5 inches of dry detention pre-treatment must be provided:

$$= 0.5 \text{ inches} \times (\text{Total Site Area} - \text{Water} / \text{Retention Area})$$

$$= 0.5 \text{ inches} \times (0.100 \text{ acres} - 0.000 \text{ acres}) \times (1 \text{ foot} / 12 \text{ inches})$$

$$= \mathbf{0.004} \text{ ac-ft required for pre-treatment}$$

5. Compute credit for using one of the following systems:

a. Wet detention volume to be provided:

$$= \text{Total required detention} - \text{Pre-treatment}$$

$$= 0.019 \text{ ac-ft} - 0.004 \text{ ac-ft}$$

$$= \mathbf{0.015} \text{ ac-ft of volume required for wet detention}$$

b. Dry detention volume to be provided (75% of the total required detention volume):

$$= \text{Total required detention volume} \times 75\%$$

$$= 0.019 \text{ ac-ft} \times 0.75 \%$$

$$= \mathbf{0.014} \text{ ac-ft of volume required for dry detention}$$

c. Dry retention volume to be provided (50% of the total required detention volume):

= Total required detention volume X 50%

PZ23-1200046.019 ac-ft X 0.50 %

04/03/2024 **0.009** ac-ft of volume required for dry retention

B. SUMMARY OF WATER QUALITY COMPUTATIONS:

Item	Description	Quantity
A.1	First inch of runoff from the entire developed project site	0.008 ac-ft
A.2	2.5 inches times percent impervious for the developed project site	0.019 ac-ft
A.3	Detention volume to be treated	0.019 ac-ft
A.4	Pre-treatment required for Commercial site	0.004 ac-ft
A.6.a	Wet detention volume required	0.015 ac-ft
A.6.b	Dry detention volume required	0.014 ac-ft
A.6.c	Dry retention volume required	0.009 ac-ft

C. EXFILTRATION TRENCH COMPUTATIONS:

$$L = \frac{FS[(\%WQ)(V_{wq}) + V_{add}]}{K(H_2W + 2H_2D_u - D_u^2 + 2H_2D_s) + (1.39 \times 10^{-4})WD_u}$$

$$H_2 = 4 \text{ ft}$$

$$D_s = 2 \text{ ft}$$

$$D_u = 2 \text{ ft}$$

$$W = 12 \text{ ft}$$

$$K = 1.15e-4 \text{ cfs/ft}^2\text{-ft}$$

$$V_{wq} = 0.225 \text{ ac-in}$$

$$V_{add} = 0 \text{ ac-in}$$

$$L_{(req)} = 18.6 \text{ Feet}$$

$$\text{Rainfall Deduction} = 0.225 \text{ ac-in} / 0.10 \text{ ac} = 2.25 \text{ in.}$$

IV. CONCLUSIONS

The length of exfiltration trench required to treat the frontage drainage for NE 22nd Avenue is 18.6 feet. 61 feet of exfiltration trench is being proposed.

DA = 0.10 acres