

NOTE:
1. MAIN LINE LOCATION IS SCHEMATIC ONLY.
2. ALL CONTROL WIRE HAS TO BE IN CONDUIT IN ALL AREAS AND SLEEVED UNDER PAVING AND CONCRETE.
3. ALL VALVES AND MAINLINE HAS TO BE INSTALLED IN LANDSCAPE AREA.
4. PROVIDE 100% COVERAGE WITH 100% OVERLAP FOR ALL IRRIGATED AREA.
5. CONTRACTOR MUST RECEIVE THE WATER LEVEL AND CONDITION (IRON OR OTHER SUBSTANCES) FROM THE WELL DRILLER OR LAKE PRIOR TO ORDERING THE PUMP STATION AND VERIFY ALL ITEMS NEEDED.
6. IRRIGATION/SPRINKLER SYSTEMS AND RISERS FOR SPRAY HEADS SHALL NOT BE INSTALLED WITHIN 1 FOOT (305 MM) OF THE BUILDING SIDEWALL.


SLEEVING:
1. ALL MAINLINE, LATERAL LINE PIPING AND CONTROL CONDUIT UNDER PAVING AND CONCRETE SHALL BE INSTALLED IN SEPARATE SLEEVES.
2. ALL SLEEVES SHALL BE A MINIMUM OF TWICE (2X) THE DIAMETER OF THE PIPE TO BE SLEEVED. NO SLEEVE SHALL BE SMALLER THAN 2 INCHES.

IRRIGATION PLAN
SCALE: 1" = 20'-0"



SHEET DESCRIPTION:
IRRIGATION PLAN
PIPE & HEAD LAYOUT

SEAL:



This item has been electronically signed and sealed by DAMIAN GONZALEZ on the date adjacent to the seal using a SHA authentication code.
Printed copies of this document are not considered signed and sealed and the SHA authentication code must be verified on any electronic copies.

PROJECT: GRAND WESTERN
BEEF / CRAZY FISH
POMPANO BEACH, FLORIDA

REVISIONS:

DATE: 03/25/2024

DRAWN BY:
Damian Gonzalez PE.
CHECKED BY:

SCALE: SCALED AS SHOWN

SHEET: IP . 1