



<p>LEGEND</p> <p>CMU WALL</p> <p>CAST-IN-PLACE CONCRETE WALL</p> <p>PRECAST CONCRETE WALL</p> <p>ROOM NUMBER</p> <p>RESIDENTIAL UNIT DESIGNATION</p> <p>LOCATION OF ENLARGED UNIT PLANS, RCP, AND INTERIOR ELEVATION REFERENCES</p> <p>WALL PARTITION</p> <p>DOOR CALLOUT</p> <p>WINDOW TYPE CALLOUT</p> <p>STOREFRONT TYPE CALLOUT</p>	<p>F.E.C.</p> <p>FIRE EXTINGUISHER CABINET - SURFACE-MOUNT</p> <p>F.E.C.</p> <p>FIRE EXTINGUISHER CABINET - SEMI-RECESSED</p> <p>F.E.C.</p> <p>FIRE EXTINGUISHER CABINET - RECESSED</p> <p>1-HOUR RATING</p> <p>2-HOUR RATING</p>	<p>GENERAL NOTES</p> <p>1. REFER TO A3 SERIES FOR ENLARGED RESIDENTIAL UNIT PLANS, INTERIOR DOOR TYPES AND LOCATIONS, RESIDENTIAL UNIT RCPs, FINISH FLOOR PLAN, AND FHA PLAN.</p> <p>2. REFER TO SHEET CD SERIES FOR WALL AND FLOOR/CEILING ASSEMBLY TYPES AND ADDITIONAL INFORMATION.</p> <p>3. REFER TO A8 SERIES FOR DOOR SCHEDULES, LEGENDS, AND DETAILS.</p> <p>4. ALL SLOPES TO BE 1/4" U.O.N.</p> <p>5. REFER TO INTERIOR DRAWINGS FOR AMENITY LIGHTING AND FINISH SPECIFICATIONS.</p> <p>6. REFER TO INTERIOR DESIGN DRAWINGS FOR CONDITIONED CORRIDOR FINISHES, CONTROL JOINTS IN CORRIDOR CEILING TO BE 3/8" O.C. MAX. PROVIDE JOINTS BEGINNING AT CORRIDOR INTERSECTIONS UNLESS NOTED OTHERWISE.</p> <p>7. DOOR LOCATIONS NOT DIMENSIONED SHALL BE LOCATED AT MIDPOINT OF WALL OR 4" CLEAR FROM ADJACENT WALL CORNER TO HINGE SIDE, TYPICAL.</p>	<p>KEY PLAN</p>
--	---	--	------------------------

DRC

PZ24-12000011

07/17/2024

DYNAMIK

5801 PEACHTREE DUNWOODY RD.
BUILDING C, SUITE 200
ATLANTA, GA 30328
TELEPHONE: 678-506-8830
DYNAMIKDESIGN.COM

CONSULTANT:

Digitally signed by David Yung
Date: 2024.08.06 14:00:58 -0400

PROJECT NUMBER: CLR2023-03

ATLANTIC ONE

1726 E ATLANTIC BLVD
POMPANO BEACH, FL 33060

CLIENT:

220 MAIN ST
GAINESVILLE, FL 32601

THE COLLIER COMPANIES

DRAWING RELEASE

DRC

DATE

06/11/2024

TITLE:

BUILDING 1000 - LEVEL 02-05

SHEET NUMBER:

A1-12

© COPYRIGHT 2024 DYNAMIK DESIGN