

WATER/SEWER NOTES -

- ALL MATERIALS & CONSTRUCTION SHALL BE IN ACCORDANCE W/ COUNTY HEALTH DEPARTMENT UTILITY STANDARDS & SPECIFICATIONS HAVING JURISDICTION.
- ALL APPLICABLE PERMITS MUST BE OBTAINED PRIOR TO COMMENCEMENT OF CONSTRUCTION (F.D.O.T., HEALTH DEPARTMENT, CITY ENG. DEPT., ETC.).
- CONTRACTOR TO VERIFY THE LOCATION OF ALL EXISTING UTILITIES IN THE FIELD AND REPORT ANY CONFLICTS WITH THE PROPOSED UTILITIES TO THE ENGINEER PRIOR TO THE START OF CONSTRUCTION.
- ALL UNDERGROUND UTILITIES TO BE INSTALLED BEFORE SUBGRADE IS STARTED.
- THE CONTRACTOR SHALL BE RESPONSIBLE THROUGHOUT THE DURATION OF CONSTRUCTION FOR THE PROTECTION OF EXISTING AND NEWLY INSTALLED UTILITIES FROM DAMAGE OR DISRUPTION OF SERVICE.
- THE CONTRACTOR SHALL MAINTAIN A CURRENT, APPROVED SET OF CONSTRUCTION PLANS ON SITE.
- THE CONTRACTOR OR ENGINEER SHALL SCHEDULE INSPECTIONS AND TESTS A MINIMUM OF 24-48 HOURS IN ADVANCE.
- WATER MAINS SHALL BE PVC OR DIP AS INDICATED ON THE PLAN SHEET. PVC PIPE SHALL CONFORM TO ANSI/AWWA C900 (SDR 18)... 36" MIN. COVER FOR PVC... 30" MIN. COVER FOR DIP.

- SEWER PIPE SHALL BE PVC ASTM D3034-73 W/SDR 35 LATEST REVISION, WITH PUSH-ON RUBBER GASKET JOINTS.
- CONTRACTOR TO SUBMIT FIVE (5) COPIES OF SHOP DRAWINGS FOR ALL STRUCTURES.
- CONTRACTOR SHALL FURNISH COMPLETE "AS-BUILT" INFORMATION SIGNED & SEALED BY A REGISTERED FLORIDA PLS TO THE ENGINEER PRIOR TO FINAL ACCEPTANCE.
- DISINFECTION OF NEW WATER MAINS SHALL BE PERFORMED IN CONFORMANCE WITH THE ANSI/AWWA C651-05 STANDARD.
- ALL CONNECTIONS TO EXISTING MAINS SHALL BE MADE UNDER THE DIRECTION OF WATER & SEWER AUTHORITY HAVING JURISDICTION.
- NO PHYSICAL CONNECTION OF NEW WATER MAINS TO ACTIVE MAINS SHALL BE MADE UNTIL SUCH TIME THAT THE NEW MAINS ARE DETERMINED TO BE BACTERIOLOGICALLY SAFE.
- CONNECTIONS TO EXISTING MAINS, OPENING/CLOSING OF EXISTING VALVES SHALL BE MADE UNDER THE DIRECTION OF THE UTILITY DEPARTMENT AND/OR AGENCIES HAVING JURISDICTION.
- CLEANOUTS SHALL BE INSTALLED AT ALL SEWER SERVICES EXCEEDING 75' IN LENGTH (I.E. EVERY 75' O.C.), WITH A CLEANOUT AT THE PROPERTY LINE, EASEMENT LINE, OR SET 5' FROM A BUILDING. THE CONTRACTOR SHALL COORDINATE THE LOCATION OF THE BUILDING CLEANOUT AND ELEVATION OF THE END SERVICE LATERAL, WITH THE BLDG. PLUMBING CONTRACTOR.



- MAX. DENSITY OF ALL OTHER BACKFILL MATERIAL SHALL BE DETERMINED BY AASHTO METHOD DESIGNATION T-99, METHOD "D", LATEST REVISION (ASTM D698)
- LAB. AND FIELD DENSITY TESTS, WHICH IN THE OPINION OF THE ENGINEER ARE NEEDED TO ESTABLISH COMPLIANCE WITH THE COMPACTION SPECIFICATIONS, SHALL BE CONDUCTED IN FIELD AND SHALL BE MADE AT SUCH DEPTHS AND LOCATIONS AS SELECTED BY THE ENGINEER, OR AS REQUESTED BY MUNICIPAL/COUNTY REVIEWING AGENCIES.
- TRENCH BACKFILL WHICH DOES NOT COMPLY WITH THE SPECIFIED DENSITIES, SHALL BE REWORKED AND RECOMPACTED UNTIL THE REQUIRED COMPACTION RATING IS OBTAINED.
- ALL WATER MAIN INSTALLATIONS SHALL COMPLY WITH THE COLOR CODING REQUIREMENTS OF CHAPTER 62-555.320.
- HYDROSTATIC TESTING OF NEW MAINS SHALL BE PERFORMED FOR A MINIMUM PERIOD OF 2 HRS., AT A MINIMUM STARTING PRESSURE OF 150 PSI. AND THE FORMULA FOR CALCULATING THE MAX. ALLOWABLE LEAKAGE BE APPLIED AS PER THE ANSI/AWWA, C600-05 STANDARD.
CURRENT ANSI/AWWA STANDARDS, PROPER FORMULA FOR DETERMINING ALLOWABLE LEAKAGE ::
 $Q = LD \times \text{SQ. ROOT OF } P / 148,000$
Q = QUANTITY OF MAKE UP WATER (GALS PER HR.)
L = LENGTH OF PIPE SECTION BEING TESTED (IN FEET)
D = NOMINAL DIAMETER OF PIPE (IN INCHES)
P = AVERAGE TEST PRESSURE DURING THE HYDROSTATIC TEST (IN PNDS. PER SQ. IN. GAUGE)

REVISIONS	BY
07-06-2022, REVISED PGD PLAN	COB
08-10-2022, REVISED W-S PLAN	COB

**SITE IMPROVEMENT PLANS FOR
POMPANO BEACH AIR PARK - PARCEL Y**
1520-1580 NE. 5th. AVENUE, POMPANO BEACH FLORIDA 33060

Charles O. Buckalew
Consulting Engineering Services, Inc.
801 South Ocean Drive, Suite 201
Hollywood, Florida 33019
C.O.A. Number: 6255
Tel. : (954) 558-1189 Fax. (954) 925-8988

DATE	MAY, 2022
SCALE	1"=30'-0"
BY	C.R.W.
JOB	MA-2285
SHT	WS-1



GENERAL PAVEMENT SECTION NOTES :
CONC. DRIVES/PARKING & PLANE PADS - 5" CONC. SLAB, 4,500 PSI., UNREINFORCED COMPACTED SUBGRADE, 15' MAX. JOINT SPACING
SIDEWALKS - 4" THK., 4,000 PSI., CONCRETE, 6" COMPACTED SAND SUBGRADE
CONC. CURBING TYPE "D" CONC. PERMITS SHALL BE SHOWN IN AREAS SHOWING STANDARD SPECIFICATION
ASPHALT DRIVES (EXIST. AS SHOWN) SHALL BE 1 1/4" TYPE S. 12" COMPACTED SUBGRADE (MIN. R-40, COMPACTED TO 98% OF PROCTOR)



Charles Buckalew
Digitally signed by Charles Buckalew
Date: 2022.08.16 09:14:48 -04'00'

DRC
PZ22-1200020
10/19/2022

DRC
PZ22-1200020
9/21/2022

This item has been Digitally Signed and Sealed by Charles O. Buckalew, FL. PE. # 24842 on August 16, 2022. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.